

DESCRIPTION

Two Stroke - Air Cooled Oil is a versatile high performance low ash engine oil for use in air-cooled 2-stroke motors. This product is formulated for use in oil injected and pre-mix systems. Two Stroke - Air Cooled Oil is recommended for 2-stroke lawnmowers, chainsaws, brushcutters, motorbikes and other similar 2-stroke engine powered implements. Recommended dilution is between 25:1 (200mL to 5L) to 50:1 (100mL to 5L), or as per manufacturers specifications. Note: This product is not suitable for use in outboard marine engines that call for a TCW 3. The fuel should be stored in well-sealed steel cans or specially designed plastic containers.

SUMMARY OF BENEFITS

- Suitable for API TA, TB, TC requirements
- Low ash formulation controls piston, port and plug cleanliness
- Contains a diluent to aid mixing with leaded and unleaded petrol

SPECIFICATIONS

- API TC
- JASO FC, FB
- TISI

SUITABLE FOR



TWO STROKE - AIR COOLED	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.865
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	66
@ 100°C	ASTM D445	cSt	9.4
TBN	ASTM D2896	Mg KOH/g	>1.1
VISCOSITY INDEX	ASTM D2270	-	>120
POUR POINT	ASTM D97	°C	-18
FLASH POINT (COC)	ASTM D92	°C	>90
SULPHATED ASH	ASTM D874	% mass	0.05
COLOUR	-	-	Green

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

205LT - #30083, 20LT - #32083, 5LT - #30583 AND 1LT - #30183