

# TECHNICAL DATA SHEET

# LAWNMOWER OIL



## DESCRIPTION

Lawnmower Oil is an SAE 30 engine oil designed for the crankcases of small 4 stroke petrol engines. Ideally suited for those engines where the manufacturer specifies a mono grade SAE 30 oil.

## SUMMARY OF BENEFITS

- Lawnmower Oil is a cost efficient oil for lawnmower engines or those requiring API SJ/CF or lower performance

## SPECIFICATIONS

- SAE VISCOSITY 30
- API SJ/CF

## SUITABLE FOR



LAWNMOWER OIL	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.878
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	95
@ 100°C	ASTM D445	cSt	11
VISCOSITY INDEX	ASTM D2270	-	105
POUR POINT	ASTM D97	°C	-18
FLASH POINT (COC)	ASTM D92	°C	224
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	5.5
SULPHATED ASH	ASTM D874	% mass	1.1
APPEARANCE	-	-	Clear Red Free Flowing

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

## AVAILABLE PACK SIZES

205LT - #30084, 20LT - #32084, 1LT - #30184

January 2023

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747  
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au