

# TECHNICAL DATA SHEET

# DEGREASER



## DESCRIPTION

Gulf Western Degreaser is a powerful multipurpose aerosol degreaser designed to remove grease and grime from numerous surfaces including engines, lawn mowers, outboard motors, concrete floors, driveways and general workshop surfaces. The Gulf Western Degreaser is formulated to quickly soften and remove grease and grime in one application leaving the surface sparkling clean.

## DIRECTIONS FOR USE

Switch engines and motors off and cover all electrical items from overspray. If possible lay fabric or cardboard paper on the floor where degreasing is to be performed so as to contain drips, accidental spillage and runny degreased products and prevent them from entering drains and waterways. Shake the can for a few seconds and spray the degreaser onto the areas to be cleaned, allow to stand for 2-3 minutes then hose off. For thick deposits of grease and grime saturate with degreaser and allow the grease to soak up degreaser for 2 minutes then hose off. For hard grime use brush or high pressure cleaner.

## CAUTION

Do not spray onto hot engines or whilst engines are running. Avoid applying onto bitumen surfaces as it is likely to soften such surfaces and render them sticky for long periods. If sprayed onto painted surfaces then remove immediately by washing with water. Do not allow the degreaser to dry onto painted surface as it will lead to a streaky appearance. If this happens then polish the surface..

## USAGE

Under normal usage the Gulf Western Degreaser will provide up to 300 spray applications per 400 gram can. Usage will also be dependent on application technique.

## WORKABILITY

Gulf Western Degreaser contains active constituents and pure (non-recycled) solvent mix which enables the degreaser to penetrate, emulsify and soften grease immediately upon application. The solvent system is carefully chosen to lubricate the degreased metal surface and prevent dirt and dust from impregnating back into it. The degreaser leaves no residues or by-products that will require further cleaning. The softened grease should be removed as quickly as possible since the degreaser will evaporate off the grease surface with time. The degreaser will impart softness to grease up to 1 hour in mild conditions (20-25°C) and 15 minutes on hot days (temperatures exceeding 30°C).

## WARNING

Intentional misuse by deliberately concentrating or inhaling contents can be harmful or fatal. Keep in a cool dry place away from sun. Do not store above 50°C. Do not use near fire or naked flame. Do not incinerate this can even when empty. Dispose of waste residues and empty cans thoughtfully.

## PROPELLANT

Hydrocarbon.

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

## AVAILABLE PACK SIZES

400G - #64099

February 2022

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747  
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au